

Brinell Hardness Testers Model : B-3000 (H), B-3000 (O)







Sold and Serviced by : **MATRIX TESTING MACHINE SERVICES** Kalewadi, Pimpri, Pune 411017 Email : matrixtestingmachineservices@gmail.com Website : www.matrixtestingmachineservices.com



SAROJ Hardness Testers, Model : B-3000 (H) & Model : B-3000 (O) are precision engineered confirming to IS:1500-2, however B-3000 (H) & Model: B-3000 (O) are most suitable for production testing.

These machines are designed to measure hardness of castings, forgings, other metals and alloys of all kinds, hard or soft, whether flat, round or irregular in shape.



B-3000 (H)

250 to 3000 in

stages of 250

250

410

200

180

1127

450

0.33

415/50/3

NIL

B-3000 (O)

hine design & operation similar to B-3000 (H). In addition evice' with 14 x magnification provided in front of project dia pression on glass screen with a micrometer measuring h 0.01mm accuracy. The indentor swivels & projects dia of ssion immediately after unloading operation which avoids time for measurement of ball impression.

Accessories :

MODEL	B-3000 (H)	B-3000 (O)
Testing table 200 mm dia	1 pc.	1 pc.
Testing table 70 mm dia with 'V' groove for round jobs - 10 to 80 mm dia.	1 pc.	1 pc.
Ball holder 5 mm	1 pc.	1 pc.
Ball holder 10 mm	1 pc.	1 pc.
Test Block HB-5/750	1 pc.	1 pc.
Test Block HB - 10/3000	1 pc.	1 pc.
Brinell Microscope	1 pc.	NIL
Allen Spanner	7 pcs.	7 pcs.
Telescopic cover for - elevating screw protection	1 set	1 set
Instruction manual	1 Book	1 Book

Due to continuous improvement of the product, SAROJ reserves all rights to change the above specifications without any prior notice.



Sold and Serviced by : MATRIX TESTING MACHINE SERVICES

Technical Data :

Loads

Initial Load

Max. test height

Depth of throat

Max. depth of elevating screw

below base (approx.) Machine height

(approx.) Net weight

(approx.)

Drive Motor

Mains Supply

Optical Device

This	facilities	production	tes
comp	pression m	ethod.	
Taala		ta .	

kgf

kgf

mm

mm

mm

mm

kg.

HP

V/cy/ph

MODEL

В-3000 (Н)	
Machine designed with a hydraulic power pack and control circuit for effortless loading unloading operation. A dial gauge in front measure depth of ball penetration. This facilities production testing within tolerance limits by compression method.	Basic mach 'Optical Dev of ball imp system with ball impres additional ti
Technical Data :	Standard

B-3000 (O)

250 to 3000 in stages of 250

NIL

380

200

180

1185

500

0.33

415/50/3 Direct reading

optical device with

14 x magnification